

# HIGHLIGHTS

- Rotax<sup>®</sup> engine
- Continuously Variable Transmission (CVT) with engine braking
- Double A-arm front suspension
   Torsional Trailing arm Independent (TTI) rear suspension
- Visco-Lok auto-locking front differential
- 1,300-lb (590 kg) towing capacity
- 5.4-gal (20.5 L) fuel capacity
- 25-in. Carlisle Trail Wolf tires
- Surrounding Spar Technology (SST) G2 frame with Geometric Contact Control
   Multifunction digital gauge
- Steel racks with LinQ quick-attach accessory system and a combined
- 360 pounds (163.3 kg) capacity
- 2.9-gal (10.9 L) water-resistant rear compartment



ENGINES 450 570 Туре 38HP, Rotax 427 cc 48HP, Rotax V-twin, single cylinder, liquid liquid cooled cooled Intelligent Throttle Control (iTC<sup>™</sup>) with Fuel Delivery System Electronic Fuel Injection (EFI) CVT, P / R / N / H / L, standard engine braking Transmission Drive Train Selectable 2WD / 4WD with Visco-Lok auto-locking front differential **Power Steering** N/A Speed Category Up to 60 km/h

#### SUSPENSIONS

| Front Suspension | Double A-arm<br>9 in. (22.9 cm) travel                               |
|------------------|--|
| Front Shocks     | Oil  |
| Rear Suspension  | Torsional Trailing arm Independent (TTI)<br>8.8 in. (22.4 cm) travel |
| Rear Shocks      | Oil  |

### **TIRES / WHEELS**

| Front Tires | Carlisle† Trail Wolf 25 x 8 x 12 in.<br>(63.5 x 20.3 x 30.5 cm)  |
|-------------|--|
| Rear Tires  | Carlisle† Trail Wolf 25 x 10 x 12 in.<br>(63.5 x 25.4 x 30.5 cm) |
| Wheels      | 12-in. steel   |
|             |  |

# BRAKES

| Front | Dual 214 mm ventilated disc brakes with<br>hydraulic twin-piston calipers |
|-------|---|
| Rear  | Single 214 mm ventilated disc brake with<br>hydraulic twin-piston caliper |

#### **DIMENSIONS / CAPACITIES**

| Estimated Dry Weight * | 678 lb (308 kg)   |
|------------------------|---|
| LxWxH                  | 83 x 46 x 49 in. (211 x 116.8 x 124 cm)   |
| Wheelbase              | 51 in. (129.5 cm)   |
| Ground Clearance       | 10.5 in. (26.7 cm)  |
| Seat Height            | 33.8 in. (85.8 cm)  |
| Rack Capacity          | Front: 120 lb (54.4 kg) /<br>Rear: 240 lb (109 kg)  |
| Storage Capacity       | Rear: 2.9 gal (10.9 L)  |
| Towing Capacity        | 750 Kg trailer with brakes and 335 kg trailer without brakes  |
| Fuel Capacity          | 5.4 gal (20.5 L)  |
| FEATURES               |   |
| Gauge                  | <ul> <li>4.5-in. digital display:</li> <li>Speedometer, tachometer, odometer, trip &amp; hour meters, gear position,</li> <li>4 x 4 indicator, temperature, engine lights, electronic fuel gauge &amp; clock</li> </ul> |
| Instrumentation        | Lighter type DC Outlet in console, standard connector in the back (15-A)  |
| Anti-theft System      | Digitally Encoded Security System (D.E.S.S.™  |
| Lighting               | 70 W from dual 35-W front light / brake light   |
| Winch                  | Prewired for available winch  |
| T-Category features    | Towing hitch with trailer plug, directional indicators, position lamps, mirrors, horn   |
| Seat                   | Standard  |
| Protection             | N/A   |

## WARRANTY

Factory warranty

2-years BRP limited warranty

©2020 Bombardier Recreational Products Inc (BRP). All rights reserved. <sup>TM</sup>, \* and the BRP logo are trademarks of Bombardier Recreational Products Inc. or its affiliates. In the U.S.A., the products are distributed by BRP US Inc. \*Base model dry weight shown. \*Visco-Lok is a trademark of GKN Viscodrive GmbH. 'All other trademarks are the property of their respective owners. For other jurisdictions, see your local dealer. Because of our ongoing commitment to product quality and innovation, BRP reserves the right, at any time, to discontinue or change specifications, prices, designs, features, models or equipment without incurring obligation. Ride responsibly. BRP highly recommends that all ATV drivers take a training course. For safety and training information, see your dealer. ATVs can be hazardous to operate. For your safety: the operator and passenger should wear a helmet, eye protection and other protective clothing. Always remember that riding and alcohol / drugs dont mix. Never engage in stunt driving. Avoid excessive speeds and be particularly careful on difficult terrain. ATVs with engine sizes of greater than 90cc are recommended for use only by those age 16 and older. Never carry passengers on any ATV not specifically designated for such use. Passenger must be at least 12 years old and able to hold handgrips and plant feet while seated against the backrest. Some models depicted may include optional equipment.

