# 2021

# *can-am*: **OUTLANDER DPS 450/570 T**

# **HIGHLIGHTS**

- Rotax® engine options
- Continuously Variable Transmission (CVT) with engine braking
- Tri-Mode Dynamic Power Steering (DPS)
- Anti-Lock Braking System (ABS)
- Double A-arm front suspension
- Torsional Trailing arm Independent (TTI) rear suspension
- 5.4-gal (20.5 L) fuel capacity
- 1,300-lb (590 kg) towing capacity
- Surrounding Spar Technology (SST) G2 frame with Geometric Contact Control
- 500-W magneto
- Multifunction digital gauge
- Steel racks with LinQ quick-attach accessory system and a combined 360 pounds (163.3 kg) capacity
- 2.9-gal (10.9 L) water-resistant rear compartment



Granite Gray

ENGINES	450	570
Туре	38HP, Rotax 427 cc single cylinder, liquid cooled	48HP, Rotax V-twin, liquid cooled
Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)	
Transmission	CVT, P / R / N / H / L, standard engine braking	
Drive Train	Selectable 2WD / 4WD with Brake Traction Control (BTC)	
Power Steering	Tri-Mode Dynamic Power Steering (DPS)	
Speed Category	More than 60 km/h	

# SUSPENSIONS

Front Suspension	Double A-arm 9 in. (22.9 cm) travel
Front Shocks	Oil
Rear Suspension	Torsional Trailing arm Independent (TTI) 8.8 in. (22.4 cm) travel
Rear Shocks	Oil

#### **TIRES / WHEELS**

Rear

Front Tires	Carlisle† Trail Wolf 25 x 8 x 12 in. (63.5 x 20.3 x 30.5 cm)	
Rear Tires	Carlisle† Trail Wolf 25 x 10 x 12 in. (63.5 x 25.4 x 30.5 cm)	
Wheels	12-in cast-aluminum	
BRAKES		
Front	Dual 214 mm ventilated disc brakes with	

Estimated Dry Weight *	678 lb (308 kg)	704 lb (319 kg)	
LxWxH	83 x 46 x 49 in. (211 x 116.8 x 124 cm)		
Wheelbase	51 in. (129.5 cm)		
Ground Clearance	10.5 in. (26.7 cm)		
Seat Height	33.8 in. (85.8 cm)		
Rack Capacity	Front: 120 lb (54.4 kg) / Rear: 240 lb (109 kg)		
Storage Capacity	Rear: 2.9 gal (10.9 L)		
Towing Capacity	750 Kg trailer with brakes and 335 kg trailer without brakes		
Fuel Capacity	5.4 gal (20.5 L)		

#### **FEATURES**

Gauge	4.5-in. digital display: Speedometer, tachometer, odometer, trip & hour meters, gear position, 4 x 4 indicator, temperature, engine lights, electronic fuel gauge & clock	
Instrumentation	Lighter type DC Outlet in console, standard connector in the back (15-A)	
Anti-theft System	Digitally Encoded Security System (D.E.S.S.™)	
Lighting	70 W from dual 35-W front light / brake light	
Winch	Prewired for available winch	
T-Category features	Towing hitch with trailer plug, directional indicators, position lamps, mirrors, horn	
Seat	Standard	
Protection	N/A	

### WARRANTY

Factory warranty 2-years BRP limited warranty

©2020 Bombardier Recreational Products Inc. (BRP), All rights reserved. <sup>104</sup>, \* and the BRP logo are trademarks of Bombardier Recreational Products Inc. or its affiliates. In the U.S.A., the products are distributed by BRP US Inc. \*Base model dry weight shown. \*Visco-Lok is a trademark of GKN Viscodrive GmbH. \*All other trademarks are the property of their respective owners. For other jurisdictions, see your local dealer. Because of our ongoing commitment to product quality and innovation, BRP reserves the right, at any time, to discontinue or change specifications, prices, designs, features, models or equipment without incurring obligation. Ride responsibly. BRP highly recommends that all ATV drivers take a training course. For safety and training information, see your dealer. ATVs can be hazardous to operate. For your safety: the operator and passenger should wear a helmet, eye protection and other protective clothing. Always remember that riding and alcohol / drugs dont mix. Never engage in stunt driving. Avoid excessive speeds and be particularly careful on difficult terrain. ATVs with engine sizes of greater than 90cc are recommended for use only by those age 16 and older. Never carry passengers on any ATV not specifically designated for such use. Passenger must be at least 12 years old and able to hold handgrips and plant feet while seated against the backrest. Some models depicted may include optional equipment.

hydraulic twin-piston calipers

Single 214 mm ventilated disc brake with

hydraulic twin-piston caliper

