



HIGHLIGHTS

- Rotax® V-Twin engine

- Rotax® V-Iwin engine
 Intelligent Throttle Control (iTC™) with riding modes
 Front and rear FOX† PODIUM† 1.5 RC2 shocks
 Continuously Variable Transmission (CVT) with engine braking
 Tri-Mode Dynamic Power Steering (DPS)
- Front, center & footwell aluminum skid plates
 A-arms MWPE protectors
- 14-in. cast-aluminum beadlock wheels
- 26-in. ITP Terracross radial tires
- Sport bumper with aluminum pre-runner
- Aluminum taper-profile handlebar with full wrap handguards
- High-strength, multifunction racks with LinQ™ quick-attach accessory system
- 625-W magneto
- 5.7-gal (21.4 L) water-resistant rear compartment
- X package coloration



ENGINE	1000R
Туре	90HP, Rotax 976 cc V-twin, liquid cooled
Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)
Transmission	CVT, P / R / N / H / L, standard engine braking
Drive Train	Selectable 2WD / 4WD with Visco-Lok QE auto-locking front differential
Power Steering	Tri-Mode Dynamic Power Steering (DPS)
SUSPENSIONS	
Front Suspension	Arched double A-arm with front sway bar 9.2 in. (23.3cm) travel
Front Shocks	FOX† 1.5 PODIUM† RC2
Rear Suspension	Torsional Trailing arm Independent (TTI) 9.9 in. (25,1 cm) travel
Rear Shocks	FOX† 1.5 PODIUM† RC2
TIRES / WHEELS	
Front Tires	ITP† Terracross 26 x 8 x 14 in. (66 x 20.3 x 35.6 cm)
Rear Tires	ITP† Terracross 26 x 10 x 14 in. (66 x 25.4 x 35.6 cm)
Wheels	14-in. cast-aluminum beadlock
BRAKES	
Front	Dual 214 mm ventilated disc brakes with hydraulic twin-piston calipers
Rear	Single 214 mm ventilated disc brake with hydraulic twin-piston caliper

DIME	NSIONS	/ CAPACI	TIES

Estimated Dry Weight *	826 lb (375 kg)
LxWxH	86 x 48 x 49.5 in.
	(218.4 x 121,9 x 126 cm)
Wheelbase	51 in. (129.5 cm)
Ground Clearance	11 in. (27.9 cm)
Seat Height	34.5 in. (87.7 cm)
Rack Capacity	Front: 100 lb (45 kg) /
	Rear: 200 lb (90 kg)
Storage Capacity	Rear: 5.7 gal (21.4 L)
Towing Capacity	1,650 lb (750 kg)
Fuel Capacity	5.4 gal (20.5 L)

FEATURES	
Gauge	7.6-in wide digital display: Speedometer, tachometer, odometer, trips & hour meters, gear position, 4 x 4 indicator, temperature, engine lights, electronic fuel gauge, clock
Instrumentation	Lighter type DC Outlet in console, standard connector in the back (15-A)
Anti-theft System	RF Digitally Encoded Security System (D.E.S.S.™)
Lighting	230 W from twin 60-W projectors and dual 55-W reflectors with tail light / brake light
Winch	Prewired for available winch
Seat	Standard
Protection	Front bumper with pre-runner Aluminum taper-profile handlebar with full wrap handguards Front, center & footwell aluminum skid plates A-arms HMWPE protectors Mudquards

Factory warranty	2-years BRP limited warranty



